

Technical Specification:

Model	DT 9611	DT 7211	
Size (HxWxD)	96 X 96 X 50 mm	72 X 72 X 50 mm	
Panel Cut-out	92 X 92 mm	72 X 72 mm	
Display	3 Digit Seven Segment (RED-0.56")		
Output	1-Relay-2C0 (230V AC-5A)		
Supply	220V AC, 50 / 60 Hz		
Protection Level	IP-65(Front side) AS per IS/IEC 60529:2001		
Operating Temperature	0°C To 55°C	Relative Humidity	Up to 95% RH Non Condensing

Parameter setting:

Parameter setting is done by using Thumbwheel and Reset key

1. Left first thumbwheel is used to change parameter
2. Reset key is used to change parameter value

For parameter setting, Press Reset key then power on, Display will show by default Parameter.

Thumbwheel Value	Reset Key + Power ON
100	Operating Relay Mode (Delayed ON, Delayed OFF)
200	Counting Direction (UP & DOWN)
300	Memory (YES Or NO)
400	Auto Manual Mode 400(IF Time = 0 then manual mode is selected IF Time != 0 (Range 1- 99 SEC.) Then auto mode selected) Ex.410 means Relay Auto Reset after 10sec.
500	Enable (YES Or NO)

Note: For Power-On Timer Start Short Start Terminal