

COUNTER DIGITAL RPM INDICATOR



MODEL	CT-9000R	CT-7000R	CT-3000R	CT-56R	CT-2000R
Dimension (HxWxD) mm	96 X 96 X 42	72 X 72 X 60	48 X 96 X 85	38 X 62 X 85	36 X 72 X 76
Panel Cutout (mm)	92 X 92	68 X 68	44 X 92	31 X 54	29 X 66
INPUT	Sensor: NPN/PNP Proximity Switch (Configurable)				
	Range: 4 - 5000 RPM				
SPECIFICATION	Supply: 230V AC ± 10%, 50Hz				

DIGITAL COUNT TOTALISER



MODEL	CT-9000	CT-7000	CT-3000	CT-56G	CT-2000
Dimension (HxWxD) mm	96 X 96 X 42	72 X 72 X 60	48 X 96 X 85	38 X 62 X 85	36 X 72 X 76
Panel Cutout (mm)	92 X 92	68 X 68	44 X 92	31 X 54	29 X 66
INPUT	Sensor: NPN/PNP Proximity Switch / Micro Switch (Configurable) / 230V AC Pulse				
	Range: 0 To 999999 Count				
SPECIFICATION	Memory: Non-Volatile Memory				
	Reset: Manual Reset, Back Reset (Optional)				
	Supply: 230V AC ± 10%, 50Hz				

COUNTER

DIGITAL PRESETABLE COUNTER

With Thumbwheel Setting



MODEL	PC-9611	PC-7211
Dimension (HxWxD) mm	96 X 96 X 50	72 X 72 X 85
Panel Cutout (mm)	92 X 92	68 X 68
INPUT	NPN/PNP Proximity switch / Micro Switch (Configurable) / 230V AC Pulse / Encoder (Factory Set)	
Sensor		
Range	0 To 999	
OUTPUT	1 Relay, 2C/O, 5A , 230V AC, 12V DC SSR Output (Any one factory set)	
SPECIFICATION		
Operating Mode	Delayed ON/Delayed OFF (Configurable)	
Count Direction	Up / Down (Configurable)	
Memory	Yes / No (Configurable)	
Speed Selection	Low, Medium, Fast (Configurable)	
Supply	230V AC ± 10%, 50/60Hz	

DIGITAL PROGRAMMABLE COUNTER



MODEL	PC-9612	PC-7212	PC-4812
Dimension (HxWxD) mm	96 X 96 X 42	72 X 72 X 60	48 x 48 x 70
Panel Cutout (mm)	92 X 92	68 X 68	44 x 44
INPUT	NPN/PNP Proximity Switch / Micro Switch (Configurable) / 230V AC Pulse / Encoder (Factory Set)		
Sensor			
Range	0 - 9999 Count		
OUTPUT	1 Relay, 1 C/O, 5A , 230V AC, 12V DC SSR Output (Any one factory set)		
SPECIFICATION			
Count Direction	Up / Down (Configurable)		
Memory	Yes / No (Configurable)		
Reset	Auto / Manual Reset / Reset at back		
Supply	230V AC ± 10%, 50Hz		85-270V AC, 50/60 Hz
Note	Double set point & Scale factor Available on customer request		

COUNTER BATCH COUNTER



MODEL	BC-9611	BC-7211	BC-4811
Dimension (HxWxD) mm	96 X 96 X 42	72 X 72 X 60	48 X 48 X 70
Panel Cutout (mm)	92 X 92	68 X 68	44 X 44
INPUT	Sensor NPN/PNP Proximity Switch / Micro Switch (Configurable) / 230V AC Pulse (Factory Set)		NPN/PNP Proximity Switch / Micro Switch / 230V AC Pulse (Factory Set)
RANGE	Range Upper display range (0 -999999 Count) Lower display range (0 -9999)		Upper display range (0 -9999 Count) Lower display range (0 -9999)
OUTPUT	1 Relay+Buzzer / SSR + Buzzer (factory set)		
SPECIFICATION	Memory Non-Volatile Memory		
Reset	Auto / Manual reset / back reset		
Supply	230V AC \pm 10%, 50Hz	85-270V AC, 50/60 Hz SMPS	

LENGTH COUNTER With Proximity



MODEL	LC-9611	LC-7211	LC-4811
Dimension (HxWxD) mm	96 X 96 X 42	72 X 72 X 60	48 X 48 X 70
Panel Cutout (mm)	92 X 92	68 X 68	44 X 44
INPUT	Sensor NPN/PNP Proximity Switch (Configurable) / Encoder (Factory set)		
RANGE	0-99999.9 / 0-999999 Meter (Configurable)		0-9999 Meter (Configurable)
OUTPUT	1 Relay, 1C/O, 5A, 230V AC/12V DC SSR Output (Any one factory set)		
SPECIFICATION	MPM Range 999.9 MPM		
Diameter	0-9999.99 MM		
Memory	Non-Volatile Memory		
Reset	Auto/Manual reset facility & front and back reset facility		
Supply	230V AC \pm 10%, 50Hz	85-270V AC, 50/60 Hz SMPS	

Note : Encoder Input available as per requirement

COUNTER

PROGRAMMABLE COUNTER

Counter + RPM



MODEL	MMC-9611	MMC-7211
Dimension (HxWxD) mm	96 X 96 X 42	72 X 72 X 60
Panel Cutout (mm)	92 X 92	68 X 68
INPUT	Sensor	NPN/PNP Proximity switch / Micro Switch (Configurable) / 230V AC Pulse(Factory Set)
	Range	Upper Display Range: (0-999999 Count) , Lower Display Range: (0-9999 RPM)
OUTPUT	Output	1 Relay, 1C/O, 5A, 230V AC/12V DC SSR Output (Any one factory set)
SPECIFICATION	Memory	Non-Volatile Memory
	Reset	Auto / Manual Reset / Back reset
	Supply	230V AC \pm 10%, 50Hz

DIGITAL RPM COUNTER



MODEL	RC-9611	RC-7211	RC-4811
Dimension (HxWxD) mm	96 X 96 X 42	72 X 72 X 60	48 X 48 X 70
Panel Cutout (mm)	92 X 92	68 X 68	44 X 44
INPUT	Sensor	NPN/PNP Proximity Switch / Micro Switch (Configurable) / 230V AC Pulse / Encoder (Factory Set)	
	Range	0 - 9999 RPM	
OUTPUT	Output	1 Relay, 1 C/O, 5A , 230V AC, 12V DC SSR Output (Any one factory set)	
SPECIFICATION	Supply	230V AC \pm 10%, 50Hz	85-270V AC, 50/60 Hz
	Note	Double set point & Scale factor Available on customer request	